

Data Base : MIL - HDBK - 217F Notice 1

Environment : GB, 25°C

Input: 115V

Output: Full Load

Unit : KPSA10-05

Ver: V10

Date: 2008/7/1

CAT	TYPE	Q'ty		λp	$\lambda(\lambda p * Q'ty)$	%
5.1	Microcircuits	1	IC1	0.0332	0.0332	2.38
6.1	Diode, Fast	1	D3	0.0875	0.0875	6.27
6.1	Diode,General	1	BR1	0.0011	0.0011	0.08
6.1	Diode,General	1	D1	0.0013	0.0013	0.09
6.1	Diode,General	1	D2	0.0011	0.0011	0.08
6.1	Diode, Schottky	1	D4	0.0017	0.0017	0.12
6.1	Voltage Regulator	1	IC3	0.0110	0.0110	0.79
6.1	Diode,Zener	1	ZD2	0.0110	0.0110	0.79
6.4	Transistor MOSFET	1	Q3	0.2640	0.2640	18.92
6.11	Optocoupler	1	IC2	0.0715	0.0715	5.12
6.11	Light Emitting Diode	1	LED1	0.0013	0.0013	0.09
9.2	Resistor film	1	R4	0.0036	0.0036	0.26
9.2	Resistor film	1	R5	0.0036	0.0036	0.26
9.2	Resistor film	1	R6	0.0036	0.0036	0.26
9.2	Resistor film	1	R7	0.0031	0.0031	0.22
9.2	Resistor film	1	R8	0.0031	0.0031	0.22
9.2	Resistor film	1	R9	0.0031	0.0031	0.22
9.2	Resistor film	1	R10	0.0081	0.0081	0.58
9.2	Resistor film	1	R11	0.0033	0.0033	0.24
9.2	Resistor film	1	R12	0.0033	0.0033	0.23
9.2	Resistor film	1	R13	0.0031	0.0031	0.22
9.2	Resistor film	1	R14	0.0031	0.0031	0.23
9.2	Resistor film	1	R15	0.0031	0.0031	0.23
9.2	Resistor film	1	R16	0.0031	0.0031	0.22
9.2	Resistor film	1	R17	0.0067	0.0067	0.48
9.2	Resistor film	1	R18	0.0040	0.0040	0.29
9.2	Resistor film	1	R20	0.0031	0.0031	0.23
9.2	Resistor film	1	R21	0.0031	0.0031	0.23
9.2	Resistor film	1	ZD1	0.0031	0.0031	0.22
9.8	Resistor thermistor	1	TH1	0.0650	0.0650	4.66
9.9	Resistor Variable	1	VR1	0.1328	0.1328	9.51
10.5	Capacitor metallized	1	Z1	0.0288	0.0288	2.07
10.1	Capacitor ceramic	1	C3	0.0057	0.0057	0.41
10.1	Capacitor ceramic	1	C4	0.0049	0.0049	0.35
10.1	Capacitor ceramic	1	C5	0.0159	0.0159	1.14
10.1	Capacitor ceramic	1	C7	0.0048	0.0048	0.34
10.1	Capacitor ceramic	1	C11	0.0072	0.0072	0.51
10.1	Capacitor ceramic	1	CX1	0.0342	0.0342	2.45
10.1	Capacitor ceramic	2	CY1,CY2	0.0062	0.0123	0.88

Data Base : MIL - HDBK - 217F Notice 1

Environment : GB, 25°C

Input: 115V

Output: Full Load

Unit : KPSA10-05

Ver: V10

Date: 2008/7/1

CAT	TYPE	Q'ty		λ_p	$\lambda(\lambda_p*Q'ty)$	%
10.14	Capacitor electrolytic	1	C1	0.0824	0.0824	5.90
10.14	Capacitor electrolytic	1	C2	0.1009	0.1009	7.23
10.14	Capacitor electrolytic	1	C8	0.1143	0.1143	8.19
10.14	Capacitor electrolytic	1	C9	0.1143	0.1143	8.19
11.1	Transformer	1	T1	0.0661	0.0661	4.74
11.2	Inductive	3	L1,L2,R1	0.0084	0.0251	1.80
22.1	Fuses	1	F1	0.0100	0.0100	0.72
16.1	Circuit Board	1	PCB	0.0005	0.0005	0.04
17.1	Joint hand soldered	4	Pin	0.0003	0.0011	0.08
17.1	Joint machine soldered	123		0.0001	0.0170	1.22
Component Count =		54		Total FR =	1.3955	
				MTBF =	716,576	Hours
				MTBF=(1/Failure Rate (FR))*10 ⁶ Hours		