

DRB120-24-1

SPECIFICATIONS

PA634-01-01

ITEMS		MODEL	DRB120-24-1
1	Nominal Output Voltage	V	24
2	Maximum Output Current	A	5
3	Peak Output Current	(*12) A	6
4	Maximum Output Power	W	120
5	Peak Output Power	(*12) W	144
6	Efficiency (Typ) (115/230VAC)	(*1) %	91/93
7	Active Average Efficiency Related to ErP (Typ) (230VAC)	%	87
8	Input Voltage Range	(*2) V	85 ~ 264VAC (47-63Hz) (Withstand 300VAC Surge for 5 seconds)
9	Input Current (Typ) (115/230VAC)	(*1) A	1.2 / 0.7
10	Inrush Current (Typ) (230VAC)	(*3) A	55A
11	PFHC	-	Designed To Meet IEC61000-3-2
12	Power Factor (Typ) (115/230VAC)	(*1) -	0.98 / 0.92
13	Output Voltage Range	V	24~28
14	Ripple & Noise	(*1,4) mV	240
15	Line Regulation	(*5,6) mV	24
16	Load Regulation	(*5,7) mV	240
17	Temperature Coefficient	-	Less than 0.02% / °C
18	Over Current Protection	(*8) -	Hiccup
19	Over Voltage Protection	(*9) V	30~35
20	Hold-up Time (Typ)	(*1) ms	20
21	Leakage Current	(*10) -	< 1mA at 230VAC
22	Monitoring Signal	-	DC OK (Photocoupler Rated : 50V, 5mA), DC OK LED
23	Series Operation	-	Possible
24	Parallel Operation	-	No
25	Operating Temperature	(*11) -	-25 ~ +55°C : 100%, +70°C : 50%
26	Operating Humidity	-	5 ~ 95%RH (No dewdrop)
27	Storage Temperature	-	-40°C ~ +85°C
28	Storage Humidity	-	5 ~ 95%RH (No dewdrop)
29	Cooling	-	Convection Cooling
30	Withstand Voltage	-	Input - Output : 4243VDC (20mA), Input - FG : 2500VDC (20mA) Output - FG : 707VDC (100mA) For 1min.
31	Isolation Resistance	-	Input - FG, Input - Output and Output - FG More than 100MΩ (500VDC) at 25°C and 70%RH
32	Vibration	-	At no operating, 10 - 55Hz (sweep for 1min) 19.6m/s ² (2G) Constant, X, Y, Z 1hour each.
33	Shock/(In Package)	-	Less Than 196 m/s ² (20G)
34	Operating Altitude	-	3000m
35	Safety	-	Approved by UL60950-1, CSA22.2 No. 60950-1-07 IEC/EN60950-1, UL 62368-1, CSA C22.2 No. 62368-1-14, IEC/EN 62368-1, CSA C22.2 No.107.1-16, UL508
36	EMI	-	Designed to meet EN55011-B, EN55032-B, EN61204-3 CLASS A
37	CE	-	LVD, RoHS 2, EMC
38	Immunity	-	Designed to meet EN61000-4-2 (Level 4), -3 (Level 3), -4 (Level 4), -5 (Level 4), -6 (Level 3), -8 (Level 4), -11
39	Weight(Typ.)	g	500
40	Size (W x D x H)	mm	35 x 125 x 124 (Refer to Outline drawing)

* Read instruction manual carefully , before using the power supply unit.

=NOTES=


- *1. At Maximum Output Power, nominal input voltage, Ta = 25°C.
- *2. For cases where conformance to various safety specs (UL, CSA, EN) are required, to be described as 100-240VAC, 50/60Hz on name plate.
- *3. Not applicable for the in-rush current to Noise Filter for less than 0.2ms.
- *4. Ripple & noise are measured at 20MHz by using a 300mm twisted pair of load wires terminated with a 0.1uF Film Capacitor and a 47uF Electrolytic Capacitor.
- *5. Measure line & load regulation at output terminal.
- *6. 85 - 264VAC, constant load.
- *7. No load - Full load, constant input voltage.
- *8. Over rated current (>101%) of peak power.
- *9. Output latched shut down at no load and hiccup at any load. Manual reset by AC cycle.
- *10. Measured by each measuring method of UL and EN (at 60Hz), Ta = 25°C.
- *11. Refer to Output Derating Curve (PA634-01-02_) for details of output derating versus ambient temperature.
- *12. Operating period at peak output current is D≤35%, <10sec and 5Arms max.
- *13. All parameters not specifically mentioned are measured at 230VAC input, rated load and Ta = 25°C.

DRB120-24-1

PA634-01-02

DERATING CURVE

***COOLING : CONVECTION COOLING**

Ta (°C)	LOAD (%)	STANDARD MOUNTING
-25 ~ +55	100	
70	50	

