

**PH75A280- \***

**EVALUATION DATA**

**型式データ**

## INDEX


1. 評価方法	Evaluation Method	PAGE
1.1	測定回路 Measurement Circuits .....	T-1
(1)	静特性、過電流保護特性、出力リップル・ノイズ波形 Steady state characteristics, Over current protection (OCP) characteristics, and Output ripple and noise waveform	
(2)	過渡応答、過電圧保護特性、その他 Dynamic response, Over voltage protection (OVP) characteristics and Other characteristics	
(3)	入力サージ電流（突入電流）特性 Inrush current characteristics	
(4)	EMI 特性 Electro-Magnetic Interference characteristics	
1.2	使用測定機器 List of equipment used .....	T-3
2.	特性データ Characteristics	
2.1	静特性 Steady state data	
(1)	入力変動、負荷変動、温度変動 Line regulation, Load regulation, Temperature drift .....	T-4
(2)	出力電圧、出力リップル・ノイズ電圧 対 入力電圧 Output voltage and Output ripple and noise voltage vs. Input voltage .....	T-6
(3)	入力電流、効率 対 出力電流 Input current and Efficiency vs. Output current .....	T-8
(4)	効率 対 入力電圧 Efficiency vs. Input voltage .....	T-10
(5)	効率 対 ベースプレート温度 Efficiency vs. Base-plate temperature .....	T-12
(6)	起動、停止電圧特性 Start and Stop voltage characteristics .....	T-14
2.2	待機電力特性 Standby power characteristics .....	T-16
2.3	通電ドリフト特性 Warm up voltage drift characteristics .....	T-18
2.4	過電流保護特性 Over current protection (OCP) characteristics .....	T-20
2.5	過電圧保護特性 Over voltage protection (OVP) characteristics .....	T-22
2.6	出力立ち上がり、立ち下がり特性 Output rise and fall characteristics .....	T-24
2.7	過渡応答（負荷急変）特性 Dynamic load response characteristics .....	T-32
2.8	入力サージ電流（突入電流）特性 Inrush current characteristics .....	T-34
2.9	出力リップル・ノイズ波形 Output ripple and noise waveform .....	T-35
2.10	EMI特性 Electro-Magnetic Interference characteristics .....	T-37

## 使用記号 Terminology used


Definition		
$V_{in}$	..... 入力電圧	Input voltage
$V_o$	..... 出力電圧	Output voltage
$V_{cnt}$	..... CNT電圧	CNT voltage
$I_{in}$	..... 入力電流	Input current
$I_o$	..... 出力電流	Output current
$T_{bp}$	..... ベースプレート温度	Base-plate temperature
$T_a$	..... 周囲温度	Ambient temperature
$f$	..... 周波数	Frequency

1. 評価方法 Evaluation Method  
 1.1 測定回路 Measurement Circuits


- (1) 静特性、過電流保護特性、出力リップル・ノイズ波形  
 Steady state characteristics, Over current protection (OCP) characteristics,  
 and Output ripple and noise waveform



- (2) 過渡応答、過電圧保護特性、その他  
 Dynamic response, Over voltage protection (OVP) characteristics  
 and Other characteristics




- (3) 入力サージ電流（突入電流）特性  
 Inrush current characteristics




- |  |                                    |
|--|------------------------------------|
| C1 : 22uF Electrolytic Capacitor           | C4 : 4700pF Ceramic Capacitor      |
| C2 : 2.2μF Ceramic Capacitor               | C5 : 8000uF Electrolytic Capacitor |
| C3 : 5V-2200uF Electrolytic Capacitor      | R1 : 50 Ω                          |
| : 12V-560uF Electrolytic Capacitor         | R2 : 0.01 Ω                        |
| : 24V-220uF Electrolytic Capacitor         |                                    |
| : 48V-220uF×2series Electrolytic Capacitor |                                    |

(4) EMI特性 Electro-Magnetic Interference characteristics

(a) 雑音端子電圧 (帰還ノイズ) Conducted Emission Noise




(b) 雑音電界強度 (輻射ノイズ) Radiated Emission Noise



\* 入出力ケーブルとしてシールドケーブルを使用  
Shielded cable used to input and output cable.

VCCI class A対応アプリケーションシステム  
VCCI class A application system



C1, C2 : 470pF Ceramic Capacitor

C3 : 1.5μF Film Capacitor

C4 : 1.5μF Film Capacitor

C5, C6 : 2200pF Ceramic Capacitor

C7 : 22μF Electrolytic Capacitor

C8 : 0.022μF Ceramic Capacitor

C9 : 2.2μF Ceramic Capacitor

C10 : 5V-2200μF Electrolytic Capacitor

: 12V-560μF Electrolytic Capacitor

: 24V-220μF Electrolytic Capacitor

: 48V-220μF×2series Electrolytic Capacitor

L1 : 0.6mH

L2 : 3.0mH

## 1.2 使用測定機器 List of equipment used

	EQUIPMENT USED	MANUFACTURER	MODEL NO.
1	AC POWER SUPPLY	KIKUSUI	PCR2000L
2	DYNAMIC DUMMY LOAD	Chrome	63030
3	DUMMY LOAD	ARCOL	HS50 SERIES
4	DATA ACQUISITION / SWITCH UNIT	AGILENT	34970A
5	SHUNT RESISTER	YOKOGAWA ELECT.	2215
6	CONTROLLED TEMP. CHAMBER	ESPEC CORP.	SH-661
7	DIGITAL STORAGE OSCILLOSCOPE	YOKOGAWA	DLM2054
8	CURRENT PROBE	YOKOGAWA	701932
9	EMI TEST RECEIVER SPECTRUM ANALYZER	ROHDE & SCHWARZ	ESCI
10	PRE AMP.	SONOMA	310N
11	AMN	SCHWARZBECK	NNLK8121
12	ANTENNA(BI-LOG ANTENNA)	TESEQ	CBL6111D

## 2. 特性データ Characteristics

## 2.1 静特性 Steady state data

(1) 入力変動、負荷変動、温度変動 Line regulation, Load regulation, Temperature drift

5V

## 1. Line regulation and Load regulation

Condition Tbp : 25°C

Io \ Vin	200VDC	280VDC	380VDC	425VDC	Line regulation	
0%	5.004V	5.004V	5.004V	5.004V	0mV	0.006%
50%	5.005V	5.004V	5.004V	5.004V	1mV	0.020%
100%	5.005V	5.004V	5.004V	5.004V	1mV	0.020%
Load regulation	1mV	0mV	0mV	0mV		
	0.018%	0.009%	0.000%	0.000%		

## 2. Temperature drift

Conditions Vin : 280VDC

Io : 100%

Tbp	-40°C	+25°C	+100°C	Temperature stability	
Vo	4.974V	5.004V	5.010V	34mV	0.680%

12V

## 1. Line regulation and Load regulation

Condition Tbp : 25°C

Io \ Vin	200VDC	280VDC	380VDC	425VDC	Line regulation	
0%	11.994V	11.994V	11.994V	11.994V	0mV	0.001%
50%	11.991V	11.991V	11.987V	11.986V	5mV	0.042%
100%	11.991V	11.991V	11.989V	11.987V	4mV	0.033%
Load regulation	3mV	3mV	7mV	8mV		
	0.025%	0.025%	0.058%	0.067%		

## 2. Temperature drift

Conditions Vin : 280VDC

Io : 100%

Tbp	-40°C	+25°C	+100°C	Temperature stability	
Vo	11.921V	11.991V	11.982V	70mV	0.583%

(1) 入力変動、負荷変動、温度変動 Line regulation, Load regulation, Temperature drift

24V

1. Line regulation and Load regulation Condition Tbp : 25°C

Io \ Vin	200VDC	280VDC	380VDC	425VDC	Line regulation	
0%	23.898V	23.898V	23.898V	23.898V	0mV	0.001%
50%	23.890V	23.893V	23.887V	23.884V	9mV	0.037%
100%	23.890V	23.892V	23.884V	23.881V	11mV	0.046%
Load regulation	8mV	6mV	14mV	17mV		
	0.033%	0.025%	0.058%	0.071%		

2. Temperature drift

Conditions Vin : 280VDC

Io : 100%

Tbp	-40°C	+25°C	+100°C	Temperature stability	
Vo	23.813V	23.892V	23.837V	79mV	0.330%

48V

1. Line regulation and Load regulation Condition Tbp : 25°C

Io \ Vin	200VDC	280VDC	380VDC	425VDC	Line regulation	
0%	47.770V	47.767V	47.767V	47.768V	3mV	0.006%
50%	47.757V	47.758V	47.758V	47.759V	2mV	0.004%
100%	47.755V	47.755V	47.755V	47.756V	1mV	0.003%
Load regulation	15mV	12mV	12mV	12mV		
	0.031%	0.025%	0.025%	0.025%		

2. Temperature drift

Conditions Vin : 280VDC

Io : 100%


Tbp	-40°C	+25°C	+100°C	Temperature stability	
Vo	47.662V	47.755V	47.797V	135mV	0.282%

(2) 出力電圧、出力リップル・ノイズ電圧 対 入力電圧


Output voltage and Output ripple and noise voltage vs. Input voltage

Conditions  $I_o$  : 100 %  
 $T_{bp}$  : -40 °C ---  
 : 25 °C - · - · -  
 : 100 °C ———

5V



12V






(2) 出力電圧、出力リップル・ノイズ電圧 対 入力電圧


Output voltage and Output ripple and noise voltage vs. Input voltage

Conditions  $I_o$  : 100 %  
 $T_{bp}$  : -40 °C ---  
 : 25 °C -.-  
 : 100 °C —

24V



48V




(3) 入力電流、効率 対 出力電流


Input current and Efficiency vs. Output current

Conditions Vin : 200 VDC - - - -  
 : 280 VDC - · - · -  
 : 380 VDC ————  
 : 425 VDC - · · · · ·  
 Tbp : 25 °C

5V



12V




(3) 入力電流、効率 対 出力電流


Input current and Efficiency vs. Output current

Conditions Vin : 200 VDC - - - -  
 : 280 VDC - · - · -  
 : 380 VDC ————  
 : 425 VDC - · · · ·  
 Tbp : 25 °C

24V




48V




(4) 効率 対 入力電圧  
Efficiency vs. Input voltage

Conditions Io : 50 %    - - - -  
                  : 100 %    ————  
                  Tbp : 25 °C

5V




12V




(4) 効率 対 入力電圧  
Efficiency vs. Input voltage

Conditions Io : 50 %    - - - -  
                  : 100 %    ————  
                  Tbp : 25 °C

24V




48V




(5) 効率対ベースプレート温度  
Efficiency vs. Base-plate temperature

Conditions  $V_{in}$  : 280 VDC  
 $I_o$  : 100 %

5V




12V




(5) 効率対ベースプレート温度  
Efficiency vs. Base-plate temperature

Conditions Vin : 280 VDC  
Io : 100 %

24V



48V



(6) 起動、停止電圧特性  
Start and Stop voltage characteristics


出力電圧 対 入力電圧  
Output voltage vs. Input voltage

Conditions  $I_o$  : 100 %  
 $T_{bp}$  : 25 °C


入力電流 対 入力電圧  
Input current vs. Input voltage

Conditions  $I_o$  : 100 %  
 $T_{bp}$  : 25 °C


5V




5V



12V



12V





(6) 起動、停止電圧特性  
Start and Stop voltage characteristics


出力電圧 対 入力電圧  
Output voltage vs. Input voltage

Conditions  $I_o$  : 100 %  
 $T_{bp}$  : 25 °C


入力電流 対 入力電圧  
Input current vs. Input voltage

Conditions  $I_o$  : 100 %  
 $T_{bp}$  : 25 °C


24V




24V



48V




48V




2.2 待機電力特性  
Standby power characteristics

Conditions Tbp : 25 °C

5V




12V




2.2 待機電力特性  
Standby power characteristics

Conditions Tbp : 25 °C

24V



48V



## 2.3 通電ドリフト特性

Warm up voltage drift characteristics


Conditions

Vin : 280 VDC


Io : 100 %

Ta : 25 °C

5V



12V



## 2.3 通電ドリフト特性

Warm up voltage drift characteristics


Conditions

Vin : 280 VDC


Io : 100 %

Ta : 25 °C

24V



48V



2.4 過電流保護特性

Over current protection (OCP) characteristics

入力電圧依存性

Input voltage dependence


Conditions Vin : 200 VDC -----  
 : 280 VDC -.-.-.-  
 : 380 VDC ————  
 : 425 VDC -·-·-·-  
 Tbp : 25 °C

ベースプレート温度依存性


Base-plate temperature dependence

Conditions Vin : 280 VDC  
 Tbp : -40 °C -----  
 : 25 °C -.-.-.-  
 : 100 °C ————


5V




5V



12V



12V



2.4 過電流保護特性

Over current protection (OCP) characteristics

入力電圧依存性

Input voltage dependence


Conditions Vin : 200 VDC -----  
 : 280 VDC -.-.-.-  
 : 380 VDC —————  
 : 425 VDC -·-·-·-  
 Tbp : 25 °C

ベースプレート温度依存性


Base-plate temperature dependence

Conditions Vin : 280 VDC  
 Tbp : -40 °C -----  
 : 25 °C -.-.-.-  
 : 100 °C —————


24V




24V



48V



48V



2.5 過電圧保護特性


Over voltage protection (OVP) characteristics

Conditions:  $V_{in}$  : 280VDC


$I_{out}$  : 0%

$T_a$  : 25°C

5V



12V






2.5 過電圧保護特性


Over voltage protection (OVP) characteristics

Conditions:  $V_{in}$  : 280VDC  
 $I_{out}$  : 0%  
 $T_a$  : 25°C

24V





48V





2.6 出力立ち上がり、立ち下がり特性  
Output rise and fall characteristics

Conditions Vin : 280 VDC  
Io : 0 %  
Tbp : 25 °C

5V





12V





2.6 出力立ち上がり、立ち下がり特性  
Output rise and fall characteristics

Conditions Vin : 280 VDC  
Io : 0 %  
Tbp : 25 °C

24V





48V





2.6 出力立ち上がり、立ち下がり特性  
Output rise and fall characteristics

Conditions Vin : 280 VDC  
Io : 100 %  
Tbp : 25 °C

5V





12V





2.6 出力立ち上がり、立ち下がり特性  
Output rise and fall characteristics

Conditions Vin : 280 VDC  
Io : 100 %  
Tbp : 25 °C

24V



48V



2.6 出力立ち上がり、立ち下がり特性 (ON/OFFコントロール時)

Output rise and fall characteristics with ON/OFF CONTROL



Conditions

V<sub>in</sub> : 280 VDC



I<sub>o</sub> : 0 %

T<sub>bp</sub> : 25 °C

5V



12V



2.6 出力立ち上がり、立ち下がり特性 (ON/OFFコントロール時)

Output rise and fall characteristics with ON/OFF CONTROL



Conditions

V<sub>in</sub> : 280 VDC



I<sub>o</sub> : 0 %

T<sub>bp</sub> : 25 °C

24V



48V



2.6 出力立ち上がり、立ち下がり特性 (ON/OFFコントロール時)

Output rise and fall characteristics with ON/OFF CONTROL



Conditions

$V_{in}$  : 280 VDC



$I_o$  : 100 %

$T_{bp}$  : 25 °C

5V



12V





2.6 出力立ち上がり、立ち下がり特性 (ON/OFFコントロール時)

Output rise and fall characteristics with ON/OFF CONTROL



Conditions

$V_{in}$  : 280 VDC



$I_o$  : 100 %

$T_{bp}$  : 25 °C

24V



48V



2.7 過渡応答（負荷急変）特性


Dynamic load response characteristics

Conditions


Vin : 280 VDC

Tbp : 25 °C

5V



12V



2.7 過渡応答（負荷急変）特性


Dynamic load response characteristics

Conditions


V<sub>in</sub> : 280 VDC

T<sub>bp</sub> : 25 °C

24V




48V



2.8 入力サージ電流（突入電流）特性  
Inrush current characteristics

Conditions Vin : 280 VDC  
Io : 100 %  
Tbp : 25 °C


48V




2.9 出力リップル・ノイズ波形  
Output ripple and noise waveform

Conditions       $V_{in}$  : 280 VDC  
                      $I_o$  : 100 %  
                      $T_{bp}$  : 25 °C

5V




12V




2.9 出力リップル・ノイズ波形  
Output ripple and noise waveform

Conditions       $V_{in}$  : 280 VDC  
                      $I_o$  : 100 %  
                      $T_{bp}$  : 25 °C

24V



48V



2.10 EMI特性

Electro-Magnetic Interference characteristics

(a) 雑音端子電圧 (帰還ノイズ)

Conducted Emission Noise

Conditions


Vin : 280 VDC

Io : 100 %


Tbp : 25 °C

5V

+Vin



-Vin



EN55011-A, EN55032-A, FCC Part.15 Subpart.B ClassAの限界値は、VCCI ClassAの限界値と同じ  
 Limit of EN55011-A, EN55032-A and FCC Part.15 Subpart.B ClassA are same as its VCCI ClassA.

2.10 EMI特性

Electro-Magnetic Interference characteristics

(a) 雑音端子電圧 (帰還ノイズ)

Conducted Emission Noise

Conditions


Vin : 280 VDC

Io : 100 %


Tbp : 25 °C

12V

+Vin



-Vin



EN55011-A, EN55032-A, FCC Part.15 Subpart.B ClassAの限界値は、VCCI ClassAの限界値と同じ  
Limit of EN55011-A, EN55032-A and FCC Part.15 Subpart.B ClassA are same as its VCCI ClassA.



2.10 EMI特性

Electro-Magnetic Interference characteristics

(a) 雑音端子電圧 (帰還ノイズ)

Conducted Emission Noise

Conditions


Vin : 280 VDC

Io : 100 %


Tbp : 25 °C

24V

+Vin



-Vin



EN55011-A, EN55032-A, FCC Part.15 Subpart.B ClassAの限界値は、VCCI ClassAの限界値と同じ  
 Limit of EN55011-A, EN55032-A and FCC Part.15 Subpart.B ClassA are same as its VCCI ClassA.

2.10 EMI特性

Electro-Magnetic Interference characteristics

(a) 雑音端子電圧 (帰還ノイズ)

Conducted Emission Noise

Conditions


Vin : 280 VDC

Io : 100 %


Tbp : 25 °C

48V

+Vin



-Vin



EN55011-A, EN55032-A, FCC Part.15 Subpart.B ClassAの限界値は、VCCI ClassAの限界値と同じ  
 Limit of EN55011-A, EN55032-A and FCC Part.15 Subpart.B ClassA are same as its VCCI ClassA.

2.10 EMI特性

Electro-Magnetic Interference characteristics

(b) 雑音電界強度 (輻射ノイズ)

Radiated Emission Noise

Conditions


Vin : 280 VDC

Io : 100 %


Tbp : 25 °C

5V

HORIZONTAL



VERTICAL



EN55011-A, EN55032-Aの限界値は、VCCI ClassAの限界値と同じ  
Limit of EN55011-A, EN55032-A are same as its VCCI ClassA.

2.10 EMI特性

Electro-Magnetic Interference characteristics

(b) 雑音電界強度 (輻射ノイズ)

Radiated Emission Noise

Conditions


Vin : 280 VDC

Io : 100 %


Tbp : 25 °C

12V

HORIZONTAL



VERTICAL



EN55011-A, EN55032-Aの限界値は、VCCI ClassAの限界値と同じ  
Limit of EN55011-A, EN55032-A are same as its VCCI ClassA.

2.10 EMI特性

Electro-Magnetic Interference characteristics

(b) 雑音電界強度 (輻射ノイズ)

Radiated Emission Noise

Conditions


Vin : 280 VDC

Io : 100 %


Tbp : 25 °C

24V

HORIZONTAL



VERTICAL



EN55011-A, EN55032-Aの限界値は、VCCI ClassAの限界値と同じ  
Limit of EN55011-A, EN55032-A are same as its VCCI ClassA.

2.10 EMI特性

Electro-Magnetic Interference characteristics

(b) 雑音電界強度 (輻射ノイズ)

Radiated Emission Noise

Conditions


Vin : 280 VDC

Io : 100 %


Tbp : 25 °C

48V

HORIZONTAL



VERTICAL



EN55011-A, EN55032-Aの限界値は、VCCI ClassAの限界値と同じ  
Limit of EN55011-A, EN55032-A are same as its VCCI ClassA.