

UL TEST REPORT AND PROCEDURE

Standard:	UL 62368-1, 3rd Ed, 2021-10-22 (Audio/video, information and communication technology equipment Part 1: Safety requirements) CAN/CSA C22.2 No. 62368-1:19, 3rd Ed, 2021-10-22 (Audio/video, information and communication technology equipment Part 1: Safety requirements)
Certification Type:	Component Recognition
CCN:	QQJQ2, QQJQ8 (Power Supplies for Use in Audio/Video, Information and Communication Technology Equipment)
Complementary CCN:	N/A
Product:	DC to DC Converter
Model:	DDA*** (N or I)-%-%-%-xxxx-(bbb); Where "****" represents rated output power between 0W and 999W, based on the installed dc-dc power unit's rating. N = non-isolated, I = operational insulation / isolated. %-%-% denotes number of outputs, number of modules and polarity (e.g. S1PX = single unit, positive or D2PN = dual output, two modules, one positive and one negative output) xxxx indicates a number indicating magnitude of nominal voltage set point (e.g. 1205 = one 12V and 5V) bbb indicates feature set.. e.g. (on off logic, power good feature present)
Rating:	Optional Input: 4.5 - 75 VDC range, Max 40.A; Output 0.5 - 52 VDC, 35 A Max, (Depending on DC converters employed.)
Applicant Name and Address:	TDK-LAMBDA AMERICAS INC 3000 TECHNOLOGY DR, SUITE 100 PLANO TX 75074 UNITED STATES

Issue Date: 2022-02-07

Page 2 of 8

Report Reference #

E220248-A6034-UL

Revision Date: 2023-05-23

This is to certify that representative samples of the products covered by this Test Report have been investigated in accordance with the above referenced Standards. The products have been found to comply with the requirements covering the category and the products are judged to be eligible for Follow-Up Service under the indicated Test Procedure. The manufacturer is authorized to use the UL Mark on such products which comply with this Test Report and any other applicable requirements of UL LLC ('UL') in accordance with the Follow-Up Service Agreement. Only those products which properly bear the UL Mark are considered as being covered by UL's Follow-Up Service under the indicated Test Procedure.

The applicant is authorized to reproduce the referenced Test Report provided it is reproduced in its entirety.

UL authorizes the applicant to reproduce the latest pages of the referenced Test Report consisting of the first page of the Specific Technical Criteria through to the end of the Conditions of Acceptability.

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL.

Prepared By: Oliver Trinh/Mengis Tesfay /
Project Handler

Reviewed By: Michael Lockhart / Reviewer

Supporting Documentation

The following documents located at the beginning of this Procedure supplement the requirements of this Test Report:

A. Authorization - The Authorization page may include additional Factory Identification Code markings.

B. Generic Inspection Instructions -

- i. Part AC details important information which may be applicable to products covered by this Procedure. Products described in this Test Report must comply with any applicable items listed unless otherwise stated in the body of this Test Report.
- ii. Part AE details any requirements which may be applicable to all products covered by this Procedure. Products described in this Test Report must comply with any applicable items listed unless otherwise stated in the body of each Test Report.
- iii. Part AF details the requirements for the UL Certification Mark which is not controlled by the technical standard used to investigate these products. Products are permitted to bear only the Certification Mark(s) corresponding to the countries for which it is certified, as indicated in each Test Report.

Product Description

The DC to DC converter DDA product family consists of PCB, one or two separately certified DC-DC converter modules and installed in a mounting DIN enclosure. The enclosure is intended to be purchased and mounted on a DIN rail and used as a component in an end-user's power system. The equipment shall be supplied from a DC source that provides double/reinforced insulation from AC mains.

Model Differences

All models within series constructed the same except for the internal DC to DC converter module employed. Rating and model designation are also dependent on converter module employed.

Test Item Particulars

Product group	end product
Classification of use by	Ordinary person
Supply Connection	not mains connected: ES1
Supply tolerance	None
Supply connection – type	Not directly connected to Mains. For building in
Considered current rating of protective device	N/A - Consider in end product installation. A;
Equipment mobility	for building-in
Over voltage category (OVC)	OVC II OVC II
Class of equipment	Not Classified
Special installation location	N/A 0
Pollution degree (PD)	PD 2
Manufacturer's specified T _{ma} (°C)	25°C
IP protection class	IPX0
Power systems	not AC mains
Altitude during operation (m)	2000 m or less
Altitude of test laboratory (m)	2000 m or less
Mass of equipment (kg)	0.25kg

Technical Considerations

- The product was submitted and evaluated for use at the maximum ambient temperature (Tma) permitted by the manufacturer’s specification of : 25°C
- The product is intended for use on the following power systems : No direct connection
- Considered current rating of protective device as part of the building installation (A) : To be considered in end product installation.
- Mains supply tolerance (%) or absolute mains supply : No direct connection
- The equipment disconnect device is considered to be : No direct connection to Mains
- The following are available from the Applicant upon request : Installation (Safety) Instructions / Manual
- The product was investigated to the following additional standard : EN IEC 62368-1:2020+A11:2020

Engineering Conditions of Acceptability

For use only in or with complete equipment where the acceptability of the combination is determined by UL LLC. When installed in an end-product, consideration must be given to the following:

- The following output circuits are at ES1 energy levels : None
- The following output circuits are at PS3 energy levels : All
- The maximum investigated branch circuit rating is : To be considered in end product installation.
- The investigated Pollution Degree is : 2
- The following end-product enclosures are required : Electrical, Fire
- The maximum continuous power supply output (Watts) relied on forced air cooling from : 504 W fan at 30.5 cfm applied to 63 cm away on the side of unit.
- The power supply was evaluated to be used at altitudes up to : "2,000 m"
- The output voltage range will be between 0.6V and 40Vdc
- depending upon the converter employed.

Additional Information

This report is based on CB report references E220248-A6001-CB-1, Amendment 1, and Correction 1, with CB Test Certificate Ref. US-32195-UL, US-32195-M1-UL, and US-32195-A1-UL respectively, which was previously evaluated to UL 62368-1, 2nd Edition, 2014-12-01, CSA C22.2 No. 62368-1- 14, 2nd Edition, 2014-12, and IEC 62368-1:2014.

Testing conducted in accordance with UL 62368-1, 2nd Edition, 2014-12-01, CSA C22.2 No. 62368-1-14, 2nd Edition, 2014-12, and IEC 62368-1:2014, was deemed equivalent to the test required per UL62368-1, 3rd Ed December 13, 2019; CAN/CSA-C22.2 No. 62368-1, 3rd Ed December 13, 2019; and IEC62368-1:2018, 3rd Ed.

All original sample and test dates are noted in the testing portion of this report.

The nameplate included in the report is representative of all models covered under this report.

Additional Standards

The product fulfills the requirements of: EN IEC 62368-1:2020+A11:2020

Markings and Instructions

Clause Title	Marking or Instruction Details
Equipment identification marking – Manufacturer identification	Listee’s or Recognized Company’s name, Trade Name, Trademark or File Number

Equipment identification marking – model identification	Model Number
<p>Special Instructions to UL Representative</p> <p>Units can be fully manufactured in either the Malaysia or Plano, TX location; however, it is also possible that completed units can go back to either factory for rework where a new product label can be applied based on the location that completed the rework.</p> <p>The Field Inspector should verify that the reworked units came from the original manufacturer (the Factory ID (if any) should be verified). The Field Inspector should verify that the new product label includes all required markings as shown in the Markings and Instructions section.</p>	