



CONNECTORS USED :

| PART DESCRIPTION       | PART NAME        | MANUFACT. | QTY |
|------------------------|------------------|-----------|-----|
| PIN HEADER (CN1 & CN2) | B6P-VH(LF)(SN)   | J.S.T.    | 2   |
| PIN HEADER (CN3)       | B6B-XH-A(LF)(SN) | J.S.T.    | 1   |

MATCHING HOUSINGS, PINS & TOOL (NOT INCLUDED WITH THE PRODUCT):

| PART DESCRIPTION           | PART NAME     | MANUFACT. | QTY |
|----------------------------|---------------|-----------|-----|
| SOCKET HOUSING (CN1 & CN2) | VHR-6N        | J.S.T.    | 2   |
| SOCKET HOUSING (CN3)       | XHP-6         | J.S.T.    | 1   |
| TERMINAL PINS              | SVH-41T-P1.1  | J.S.T.    | 12  |
| TERMINAL PINS              | SXH-002T-P0.6 | J.S.T.    | 6   |

NOTES

- A. MODEL NAME, INPUT VOLTAGE RANGE, NOMINAL OUTPUT VOLTAGE, MAXIMUM OUTPUT CURRENT, BUFFER TIME, COUNTRY OF MANUFACTURE AND SAFETY MARKING (FOR ONLY APPROVED PRODUCTS) ARE SHOWN HERE IN ACCORDANCE WITH THE SPECIFICATIONS.
- B. CUSTOMER'S CHASSIS MOUNTING: HOLE : 3-φ4.5 HOLES AND 4-φ4.5 SLOT & 7-M4 THRU HOLE .
- C. SWITCH IS SELECTED TO FIXED MODE BEFORE SHIPMENT. (SWITCH IS FOR 24V ONLY).

(unit : mm)

|                   |         |
|-------------------|---------|
| MODEL NAME        | ZBM20/L |
| <b>TDK-Lambda</b> |         |
| PA642-02-01/L-A   |         |